

## KUPER SWT XL



Perfect for crafts and industry, with many individual options

### Specifications:

Description:	Standard:	Optional possibilities:
Working width	15 up to 230mm	10 up to 350mm
Working height	10 up to 150mm	5 up to 230mm
Feed speed	6 up to 24m/min	2 up to 60m/min
Axial adjustment range	Horizontalspindle 20mm Vertikalspindle 60mm	Horizontalspindle up to 60mm Vertikalspindle up to 80mm
Spindle configurations	1 up to 10 spindles	
Spindle motor power	Bottom and right 5,5KW	Bottom up to 18KW Right up to 11KW
	Left and top 7,5KW	Left up to 11KW Top up to 18,5KW
Universalspindle	7,5KW	Up to 11KW
Sawspindle	11KW	Up to 30KW
Spindle rpm	6.000U/min	2.000 up to 9.000U/min
Spindle diameter	40mm	50mm
Tool diameter	112 to 200mm (First top spindle 125-160mm)	Bottom side up to 250mm
Cutting depth for profiles	Up to 20mm (bottom 14mm)	Up to 35mm

### Standard equipment:

- Quick clamping system "Pro Lock"
- Hard chrome surface on all table plates
- Feed speed individually adjustable via frequency
- Continuous feed strand, power transmission via worm gear and propeller shaft
- Feeded double mounted in- and outfeed rollers in the machine table
- Hand pump for table lubrication
- Electronic start-stop system for spindle motors
- Feed- and spindle motors performed as IE2 energy efficient motors
- Pneumatically absorbed pressure shoe behind the upper spindle improved dynamically by lineal guides
- Electrically height adjustment of the feed beam

