

KUPER SWT XS



Perfect for crafts, with the possibility of profiling

Specifications:

Description:	Standard:
Working width	15 up to 230mm
Working height	10 up to 125mm
Feed speed	6 up to 24m/min
Axial adjustment range	Horizontalspindle 20mm Vertikalspindle 20mm
Spindle configurations	4, 4+U, 5
Spindle motor power	Bottom and top 5,5KW
	Right and left 7,5KW (one motor for both spindles)
Universalspindle	7,5KW
Spindle rpm	6.000U/min
Spindle diameter	40mm
Tool diameter	First bottom 125 up to 160mm
	Vertical 125 up to 180mm
	Top 112 up to 200mm
	Bottom 112 up to 200mm
Cutting depth for profiles	Up to 20mm

Standard equipment:

- Quick clamping system "Pro Lock"
- Hard chrome surface on all table plates
- Feed speed individually adjustable via frequency
- Continuous feed strand, power transmission via worm gear and propeller shaft
- Feeded double mounted in- and outfeed rollers in the machine table
- Hand pump for table lubrication
- Electronic start-stop system for spindle motors
- Feed- and spindle motors performed as IE2 energy efficient motors
- Pneumatically absorbed pressure shoe behind the upper spindle improved dynamically by lineal guides
- Electrically height adjustment of the feed beam

