



The CML Advanced Series is tailored to meet from low to high volume production requirements. With the Advanced Series, you get the features you need, without paying for extras you don't. The SCA 450 RT 500 series features a heavy-duty 3 or 4 moving blade solution with higher horsepower ratings for higher volume customers, Advanced series machines includes others horsepower that provides different cutting area with possibilities in high volume environments. Whatever your requirements, Cml offers an edger to meet your needs.

CML

Cml has industry-leading edgers to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML edger optimize materials and minimize costs. CML edgers deliver high quality cuts with limitless application possibilities. Whatever your requirements. CML has a edger to help you make the most of every situation.

Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 6 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft and moving heads
- Operator adjustable 15mw lasers
- Complete range of optimization solutions

CML ENGINEERING S.R.L.
Advanced Equipment
Intelligent Integration
Experienced Consulting
Incomparable Services
E-mail info@cml-engineering.it



Advanced Series

Edger SCA 650 RT 700

Technical Specifications	CML Edger SCA 650 RT 700
Voltage	400V / 50Hz
Dust Connection (MAIN)	300mm diameter port/30 meters per second/7600Mc3/h
Machine Weight	6500Kg
Machine Dimensions	Length 255cm Width 245cm Height 200cm
Main Drive Motor	Hp 60-75-100-125 / Kw 44-55-74-92
Feed Belt Motor	3Kw
Feed Belt Speed	0 to 50 Meters per minute
Pressure Roll Motor	0.75Kw
Maximum pass thru width	1150mm
Feed belt width	500mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	145mm (450mm Blade)
Minimum board Thickness	20mm
Minimum board Length	750mm (400mm with optional – small pieces)
Minimum board Width between fixed and moving blade	16mm
Maximum distance between fixed and moving table	470mm (both moving heads installed)
Maximum distance between fixed and moving table	600mm (only one moving heads installed)
Maximum distance between two and moving table	484mm
Table working height from floor	780mm
Control panel for cutlist with up to 99 different program (Manual or automatic control)	
Position laser control (beam color red. Power 15mw maximum range 6m)	
Nylon center feed belt guide for glue line capability at 165ft per minute	
Sound enclosure padding for quite running reducing noise level 15db	
Automatic oil pump for feed chain with failure detection shutoff	
Specifications are subject to change.	



Main Office : Via Torri Bianche 1 - 20871 VIMERCATE (MI) – ITALY

Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY

Tel 0039-02-95384207

Fax 0039-02-95384223

E-mail : info@cml-engineering.it – Web : www.cml-engineering.it